CCR COMPETITION OIL CATCH CAN

PART NO. CCR-101, CCR-105, CCR-110

MADE IN USA



Important: Read these instructions in their entirety prior to installation.

For contact information, visit www.improvedracing.com

Copyright © 2008-2024 Improved Racing Products, LLC. All rights reserved.

Rev 240709

PARTS CHECK

- Visit the website product page to confirm all parts have arrived by checking the images:

CCR-101

CCR-105

CCR-110

BEFORE YOU BEGIN

⚠ **WARNING: This product should be installed by a qualified mechanic.**

⚠ **WARNING: Improper installation could result in severe engine damage.**

SELECT AN INSTALLATION CONFIGURATION

- CCR is a vent to atmosphere catch can in standard configuration.
  - Use the kit below for recirculating installations:

- Experiment with the universal mounting bracket for placement and orientation on your vehicle to determine what hole to place the thumb screw and lanyard retainer cord onto.
  - Apply Loctite 243 prior to installing stainless hardware into the aluminum bracket and lightly tighten to feel.

INSTALLATION INSTRUCTIONS

1. Select a location to install the catch can(s) on your vehicle.
2. Secure the mounting bracket to a sturdy location on your vehicle.
3. Install the catch can into the mounting bracket.
4. Position the catch can and tighten the mounting bracket thumb screw.
5. Torque the can fittings in between 38 to 45 lb-ft (51 to 61 N-m).
6. Connect and tighten all the lines.
7. Start the vehicle and confirm there are no vacuum leaks when installed as a recirculating system.

🏁 Installation is now complete. Thank you for purchasing an Improved Racing product!

HOW TO USE & SERVICE CCR

- Watch this YouTube Short that outlines how easy our can is to use and service after installation: